

10,000 PSIG STAINLESS STEEL HOUSINGS

Features:

- 316L Stainless Steel Construction
- Pressure To 10,000 PSIG, Temperature To 900°F
- Compact Designs For Fast Response Times
- Free From Welds NACE Complaint
- Available in Hastelloy, Monel, Etc.



The 110HP and 120HP series of filters are ideal for use with gaseous and liquid sample process analyzers, fuel cell filtration, as well as other high-pressure requirements. The small internal volume, compact design, and positive O-ring sealing mechanism make them perfect for demanding analyzer applications. They are constructed entirely of 316L stainless steel and are free of welds to comply with NACE MR-01-75.

These housings are also available with a PTFE seal, which requires a modified sealing design: simply add an "S" to the housing code, e.g. 112SHP. **PTFE seals cannot be retrofitted into standard housings originally having a Viton O-ring.** A high temperature gasket can only be fitted into the S version housing.

Applications:

- Alternative Fuel Protection
- Injection Pumps
- CNG Boosters

PRINCIPLE SPECIFICATIONS

Housing Model w/ Drain	110HP	112HP	120HP	122HP
Housing Model w/o Drain	114HP	116HP	124HP	126HP
Port Size (NPT)	1/8"	1/4"	1/8"	1/4"
Drain Type (NPT)	1/8"	1/4"	1/8"	1/4"
Maximum Pressure (psig) (1)	10,000	10,000	10,000	10,000
Internal Volume (cc)	26	26	40	40
Maximum Temp. -Buna-N (250°F)	BN110HP	BN110HP	BN110HP	BN110HP
Maximum Temp. -EPDM (300°F)	GE110HP	GE110HP	GE110HP	GE110HP
Maximum Temp. -Viton (400°F)	GV110HP	GV110HP	GV110HP	GV110HP
Maximum Temp. -Silicone (450°F)	GS110HP	GS110HP	GS110HP	GS110HP
Maximum Temp. -PTFE (400°F)	GP110SHP	GP110SHP	GP110SHP	GP110SHP
Maximum Temp. -Kalrez (600°F)	KZ110HP	KZ110HP	KZ110HP	KZ110HP
Maximum Temp. -Carbon (900°F)	GNA110SHP	GNA110SHP	GNA110SHP	GNA110SHP
Principle Dimensions: (inches)				
Center Of Port To Head	0.86	0.86	0.86	0.86
Head Diameter	2.56	2.56	2.56	2.56
Overall Length	4.13	4.13	5.12	5.12
Element Removal Clearance	1.57	1.57	2.56	2.56
Filter Element Codes: (2)				
Disposable Element	12-32-□	12-32-□	12-57-□	12-57-□
Stainless Steel Element	SS-12-32-□	SS-12-32-□	SS-12-57-□	SS-12-57-□
PEL Element	PEL-12-32-□	PEL-12-32-□	PEL-12-57-□	PEL-12-57-□
PTFE Element	PT-12-32-□	PT-12-32-□	PT-12-57-□	PT-12-57-□
Materials Of Construction: (3)				
Head & Internals	316LSS	316LSS	316LSS	316LSS
Bowl	316LSS	316LSS	316LSS	316LSS
O-Rings (Standard)	Viton	Viton	Viton	Viton
Accessories:				
Mounting Bracket	MBSS130	MBSS130	MBSS130	MBSS130
Support Core	SC110	SC110	SC120	SC120

FLOW RATE IN SCFM FOR ABOVE ASSEMBLIES WITH GRADE 50C ⁽⁴⁾ or 70C ⁽⁵⁾

Air Line Pressure (PSIG)	110HP Series		120HP Series	
	50C	70C	50C	70C
15	2	6	3	7
30	3	9	4	10
60	4	14	7	17
100	6	23	11	27
150	9	31	15	36
250	13	47	23	56
500	25	91	44	108
1500	76	279	133	330
3000	151	557	265	659
5000	256	940	468	1118
10,000	447	1880	765	1912

- Notes: (1) Above 400°F pressure ratings are reduced, consult UFS for exact rating at specific temperature
 (2) Replace '□' with grade required, e.g. 12-32-50C, PT-12-57-03
 (3) Material abbreviations, 316LSS = 316L Stainless Steel
 (4) Flow rates for Grade 50C rated at 99.99% against 0.01 micron
 (5) Flow rates for Grade 70C rated at 95% against 0.01 micron



United Filtration Systems, Inc.
 6558 Diplomat Drive
 Sterling Heights, MI 48314
 T (586) 802-5561 • F (586) 802-5562
 sales@unitedfiltration.com
 www.unitedfiltration.com

1-800-311-5561



Partner of Headline Filters

SH110-1 / SH120-1